

SAFETY DATA SHEET

Ink cartridge (Light Cyan)

IP5-205

OKI DATA INFOTECH CORPORATION

Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	Product Name : Ink cartridge(Light Cyan) Product Code : IP5-205
1.2 Relevant identified uses of the substance or mixture and uses advised against	Inkjet Ink
1.3 Details of the supplier of the safety data sheet	
Manufacturer's Name :	OKI Data Infotech Corporation 563, Takatsuka-Shinden, Matsudo-shi, Chiba, 270-2222, Japan Tel:+81-47-391-2349
Distributor:	OKI Europe Ltd. Wide Format Division Siemensstrase 9, D-63263 Neu-Isenburg Germany +49 (0) 6102 297 400

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

<Regulation (EC) No. 1272/2008>


Classification

Skin irritation, Category 2	H315: Causes skin irritation.
Reproductive toxicity, Category 1B <1999/45/EC >	H360Df: May damage the unborn child. Suspected of damaging fertility.
Toxic to Reproduction Category 1	R61: May cause harm to the unborn child.
Toxic to Reproduction Category 3	R62: Possible risk of impaired fertility.
Irritant	R38: Irritating to skin.

2.2 Label elements

<Regulation (EC) No. 1272/2008>

Hazard pictograms



Signal word:	Danger
Hazard statements	H315 Causes skin irritation. H360Df May damage the unborn child. Suspected of damaging fertility.
Precautionary statements	
Prevention:	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:	P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

bis(2-(2-methoxyethoxy)ethyl) ether

2.3 Other hazards

Vapours may form explosive mixture with air.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Main Ingredients	Content (%)	CAS-No.	EC-No.	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)
bis(2-ethoxyethyl)ether	70-80	112-36-7	203-963-7	Xi; R38	Skin Irrit. 2; H315
bis(2-(2-methoxyethoxy)ethyl) ether	5-15	143-24-8	205-594-7	Repr.Cat.2; R61 Repr.Cat.3; R62	Repr. 1B; H360Df

Other components (listed on EINECS, NLP or ELINCS) are not hazardous according to the directives mentioned above.

4. FIRST-AID MEASURES

4.1 Description of first aid measures

General advice:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
Protection of first-aiders:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
If inhaled:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention immediately
If swallowed:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks:	Causes skin irritation. May damage the unborn child. Suspected of damaging fertility.
--------	------------------------------------------------------------------------------------------

4.3 Indication of any immediate medical attention and special treatment needed

Treatment:	Treat symptomatically and supportively
------------	----------------------------------------

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:	Water spray Alcohol-resistant foam
-------------------------------	---------------------------------------

Dry chemical
Carbon dioxide (CO2)

Unsuitable Extinguishing Media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products: Carbon oxides

5.3 Advice for firefighters

Special protective equipment for fire-fighters: In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Cool containers/tanks with water spray.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions: Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up: Non-sparking tools should be used.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Technical measures:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation:	Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling:	Do not get on skin or clothing. Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:	Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Advice on common storage:	Do not store with the following product types: Strong oxidizing agents Explosives Gases

7.3 Specific end use(s)

Specific use(s):	No data available
------------------	-------------------

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

bis(2-ethoxyethyl)ether:	End Use: Workers
	Exposure routes: Inhalation
	Potential health effects: Long-term systemic effects
	Value: 50.5 mg/m ³
	End Use: Workers
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
	Value: 3.43 mg/kg bw/day
	End Use: Consumers
Exposure routes: Inhalation	
	Potential health effects: Long-term systemic effects
	Value: 5.96 mg/m ³
End Use: Consumers	
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
Value: 1.71 mg/kg bw/day	

End Use: Consumers
 Exposure routes: Ingestion
 Potential health effects: Long-term systemic effects
 Value: 300 mg/kg bw/day

bis(2-(2-methoxyethoxy)ethyl) ether: End Use: Workers
 Exposure routes: Inhalation
 Potential health effects: Long-term systemic effects
 Value: 22 mg/m³
 End Use: Workers
 Exposure routes: Skin contact
 Potential health effects: Long-term systemic effects
 Value: 3 mg/kg bw/day
 End Use: Consumers
 Exposure routes: Inhalation
 Potential health effects: Long-term systemic effects
 Value: 0.5 mg/m³
 End Use: Consumers
 Exposure routes: Skin contact
 Potential health effects: Long-term systemic effects
 Value: 0.001 mg/kg bw/day
 End Use: Consumers
 Exposure routes: Ingestion
 Potential health effects: Long-term systemic effects
 Value: 0.001 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis(2-(2-methoxyethoxy)ethyl) ether: Fresh water
 Value: 32 mg/l
 Marine water
 Value: 3.2 mg/l
 Intermittent use/release
 Value: 50 mg/l
 Sewage treatment plant
 Value: 500 mg/l
 Fresh water sediment
 Value: 127 mg/kg
 Marine sediment
 Value: 12.7 mg/kg
 Soil
 Value: 6.7 mg/kg
 Oral
 Value: 8.32 mg/kg

8.2 Exposure controls

Engineering measures: Minimize workplace exposure concentrations.
 Use only in an area equipped with explosion proof exhaust ventilation.
 Use with local exhaust ventilation.

Personal protective equipment

Eye protection: Wear the following personal protective equipment:
 Safety glasses

Hand protection

Material: Impervious gloves
 Flame retardant gloves

Remarks: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to

	chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type:	Organic vapour type (A)

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	liquid
Color:	blue
Odor	solvent-like
Odor Threshold:	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	71 °C Method: Cleveland open cup
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper explosion limit:	No data available
Lower explosion limit:	No data available
Vapour pressure:	No data available
Relative vapour density:	No data available
Density:	0.9-1.1g/cm ³ (25 °C)
Water solubility:	soluble
Solubility in other solvents	soluble Solvent: organic solvents
Partition coefficient: n-octanol/water:	Not applicable
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, dynamic:	5 - 15 mPa.s (25 °C)
Explosive properties:	Not explosive
Oxidizing properties:	The substance or mixture is not classified as oxidizing.

9.2 Other information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions: Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid: Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid: Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure: Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity: Not classified based on available information.

<Bis(2-ethoxyethyl) ether>

Acute oral toxicity: LD50 (Rat): 4,970 mg/kg

<bis(2-(2-methoxyethoxy)ethyl) ether>

Acute oral toxicity: LD50 (Rat): 3,850 mg/kg

Acute dermal toxicity: LD50 (Rat): > 6,900 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation: Causes skin irritation.

<Bis(2-ethoxyethyl) ether>

Result: Skin irritation

Remarks: Based on data from similar materials

<bis(2-(2-methoxyethoxy)ethyl) ether>

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation:

Not classified based on available information.

<Bis(2-ethoxyethyl) ether>

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

<bis(2-(2-methoxyethoxy)ethyl) ether>

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitization:	Not classified based on available information.
Respiratory sensitisation:	Not classified based on available information.
<Bis(2-ethoxyethyl) ether>	
Test Type:	Local lymph node assay (LLNA)
Exposure routes:	Skin contact
Species:	Mouse
Method:	OECD Test Guideline 429
Result:	negative
Remarks:	Based on data from similar materials
<bis(2-(2-methoxyethoxy)ethyl) ether>	
Test Type:	Local lymph node assay (LLNA)
Exposure routes:	Skin contact
Species:	Mouse
Method:	OECD Test Guideline 429
Result:	negative
Remarks:	Based on data from similar materials
Germ cell mutagenicity	Not classified based on available information.
<Bis(2-ethoxyethyl) ether>	
Genotoxicity in vitro	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
<bis(2-(2-methoxyethoxy)ethyl) ether>	
Genotoxicity in vitro	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Carcinogenicity	Not classified based on available information.
Reproductive toxicity	May damage the unborn child. Suspected of damaging fertility.
<Bis(2-ethoxyethyl) ether>	
Effects on fertility	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
Effects on foetal development	Test Type: Embryo-foetal development Species: Rabbit Application Route: Ingestion Result: negative
<bis(2-(2-methoxyethoxy)ethyl) ether>	
Effects on fertility	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 421 Result: positive
Effects on foetal development	Test Type: Embryo-foetal development Species: Rabbit Application Route: Ingestion Method: OECD Test Guideline 414 Result: positive
Reproductive toxicity - Assessment	Clear evidence of adverse effects on development, based on animal experiments., Some evidence of

adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure: Not classified based on available information.

STOT - repeated exposure: Not classified based on available information.

Repeated dose toxicity

<Bis(2-ethoxyethyl) ether>

Species: Rat
 NOAEL: 2.49 mg/l
 Application Route: inhalation (dust/mist/fume)
 Exposure time: 4 w
 Method: OECD Test Guideline 412

<bis(2-(2-methoxyethoxy)ethyl) ether>

Species: Rat
 NOAEL: 250 mg/kg
 Application Route: Ingestion
 Exposure time: 28 d
 Method: OECD Test Guideline 407
 Remarks: Based on data from similar materials

Aspiration toxicity: Not classified based on available information.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

<Bis(2-ethoxyethyl) ether>

Toxicity to fish: LC50 : > 10,000 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates: LC50 : 6,600 mg/l
 Exposure time: 96 h

Toxicity to bacteria: NOEC : > 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity): EC10: 7.38 mg/l
 Exposure time: 7 d
 Species: Ceriodaphnia dubia (water flea)
 Remarks: Based on data from similar materials

<bis(2-(2-methoxyethoxy)ethyl) ether>

Toxicity to fish: LC50 (Danio rerio (zebra fish)): > 5,000 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 7,467 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae: EC50 (Pseudokirchneriella subcapitata (green algae)): 2,814 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to bacteria: EC10 : >= 5,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates :
(Chronic toxicity)

NOEC: 320 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

12.2 Persistence and degradability

<Bis(2-ethoxyethyl) ether>

Biodegradability:

Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

<bis(2-(2-methoxyethoxy)ethyl) ether>

Biodegradability:

Result: Inherently biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 302B
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

<Bis(2-ethoxyethyl) ether>

Partition coefficient: n-octanol/water: log Pow: 0.39

<bis(2-(2-methoxyethoxy)ethyl) ether>

Partition coefficient: n-octanol/water: log Pow: -0.84

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product:

Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals:

Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59):

Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants: Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances:

Not applicable

Other regulations: Take note of Dir 94/33/EC on the protection of young people at work.
Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Full text of R-Phrases

R38:Irritating to skin.

R61:May cause harm to the unborn child.

R62:Possible risk of impaired fertility.

Full text of H-Statements

H315:Causes skin irritation.

H360Df:May damage the unborn child. Suspected of damaging fertility.

Full text of other abbreviations

Repr.: Reproductive toxicity

Skin Irrit.: Skin irritation

Further information

Sources of key data used to compile the Safety Data Sheet:

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's

end product, if applicable.