



Next generation 5 Colour Digital Toner Transfer Printer

3-in-1 Applications

- 1. Digital Toner Transfer Printing** ✓
Print high quality CMYK+White designs on SRA3 transfer media and heat press onto hard and soft surfaces
- 2. Digital Screen Printing Frames** ✓
Make the production of screen printing frames faster and easier with a chemical-free process
- 3. Digital Smart Screen Transfers (DSST)** ✓
Combine digital and analogue screen printing techniques to efficiently produce durable full-colour textile decorations



Pro9541WT

Specifications

Performance		5 Colour Digital LED
Print Speed¹	CMYK+White	Up to 18 ppm for Letter Transfers and 12 ppm for A3 Transfers
Time to First Page¹		Approx. 8 seconds
Duty Cycle		300,000 pages
Print Quality	Resolution	Up to 1200 x 1200 dpi; ProQ 1200 x 600 x 16 levels
Memory	RAM (Standard/Max)	2 GB
	Processor	1.2 GHz ARM CPU
Compatibility	Printer Languages	Adobe® PostScript® 3™
	Connectivity	High-speed USB 2.0, 10 Base-T/100 Base-TX/1000 Base-T Ethernet
	Operating Systems	Windows® 7 and higher, Mac® 10.10 and higher
	Network Protocols	TCP/IP, EtherTalk
Colour Features/ Solutions		Standard Adobe PostScript 3 controller includes Trapping, ICC-based Colour Management, Simulations for SWOP, ISO Coated, Japan Colour; PDF Direct Print; PS Gamma Adjust; Colour Correct
Media Handling	Media Sizes	A3+ (329 x 483mm), A3 (297 x 420mm), legal, letter, A3, A4, A5, A6, and media up to 1,320mm
	Media Weight	Trays 1/2/3: 52-320 gsm; Multi-purpose Tray: 52-360 gsm;
Media Capacity	Multi-purpose Tray (MPT)	Up to 300 sheets
	Trays 1/2/3	Up to 530 sheets
	High-Capacity Feeder	Up to 1,590 sheets
Max Capacity		Up to 2,950 sheets (w/ MPT, 2 Trays and High-Capacity Feeder)
Media Output		Face Down: max 610 sheets; Face Up: max 300 sheets
Environmental	Size (WxDxH)	699 mm x 625 mm x 640 mm
	Weight	110.8 kg including consumables
	Temperature/Humidity	10° - 32° C / 20% - 80% RH Quality Assured Range: 17° - 27° C / 50% - 70% RH
	Power Consumption	Active: 1600W max. /1100W avg.; Standby: avg. 40W; PowerSave mode: 30W or less; Sleep mode: 4W or less; Auto Shutoff: 0.4W or less
	Noise Levels	Active: 57dBA or less; Standby: 34dBA or less; PowerSave mode: Inaudible
Options	Accessory (Part Number)	530-Sheet 2nd/3rd Tray (45530703); High-Capacity Feeder w/ caster base (45530803); 530-Sheet Tray w/ Caster Base (45530903); Cabinet (45980001); 160 GB Hard Disk Drive (44622302)

Ordering Information

Product	Description	Part Number
Pro9541WT	5 Colour Digital Transfer Printer	45530677 (230V)
Toner Cartridges	24,000 pages ² 10,000 pages ⁵	Cyan - 45536473; Magenta - 45536472; Yellow - 45536471; Black - 45536474 White - 45536475
Image Drums	40,000 pages ⁶ 20,000 pages ⁶	Cyan - 47094108; Magenta - 47094107; Yellow - 47094106; Black - 47094109 White - 47094110
Waste Toner Box	Approx. 40,000 pages ⁶	45531503
Fuser	Approx. 150,000 pages	45531113 (230V)
Transfer Belt	Approx. 150,000 pages	45531223

OKI EUROPE LTD

Blays House, Wick Road,
Egham Surrey, TW20 0HJ,
UK
T +44 (0)20 8219 2190
F +44 (0)20 8219 2199
WWW.OKI.COM/EU

For further information on OKI's unique White Toner printer portfolio visit
www.okieurope.com/white