

1258625 - Printer Vendor Wizard Note: Oki

Version	53	Type	SAP Note
Language	English	Master Language	English
Priority	Recommendations / Additional Info	Category	Special development
Release Status	Released for Customer	Released On	16.10.2017
Component	BC-CCM-PRN-PVP-OK (SAP Printer Vendor program: Oki)		

Please find the original document at [https://launchpad.support.sap.com/#/notes/ 1258625](https://launchpad.support.sap.com/#/notes/1258625)

Symptom

The company OKI is member of the SAP Printer Vendor program and offers within this program connection software support for the printer model / device type pairs listed below.

For general information about the SAP Printer Vendor program please check note 1130927.

The printer model / device type combinations are visible in the newest data version of the "device type wizard". Please read note 1036961 for a description how to use the device type wizard and how to select one of the combinations shown below.

The device types are delivered as attachments to this note. Please download the files and proceed with the installation as described in note 1103422.

Certain features of the device types become active only with the following releases and support package levels:

Additional print options: (see note 1049778)

SAP_BASIS 6.20 SP63 and higher

SAP_BASIS 6.40 SP21 and higher

SAP_BASIS 7.00 SP14 and higher

SAP_BASIS 7.10 standard

Other Terms

SPAD , device type , SAP Printer Vendor program

Solution

Supported Printer model/ device type combinations:

Number Printer model Device type Supported language

001 OKI B440 OKI440 Latin1 (ISO1)

002 OKI B430 OKI440 Latin1 (ISO1)

003 OKI B420 OKI440 Latin1 (ISO1)

004 OKI B410 OKI440 Latin1 (ISO1)

005 ES4140 OKI440 Latin1 (ISO1)

006 OKI MB460 OKI440 Latin1 (ISO1)

007 OKI MB470 OKI440 Latin1 (ISO1)

008 OKI MB480 OKI440 Latin1 (ISO1)
009 ES4160 MFP OKI440 Latin1 (ISO1)
010 ES4180 MFP OKI440 Latin1 (ISO1)
011 OKI B6500 OKIB6500 Latin1 (ISO1)
012 OKI B6250 OKIB6500 Latin1 (ISO1)
013 ES6150 OKIB6500 Latin1 (ISO1)
014 OKI B930 OKIB930 Latin1 (ISO1)
015 ES9130 OKIB930 Latin1 (ISO1)
016 OKI MC860 OKIA3NF1 Latin1 (ISO1)
017 ES8460 MFP OKIA3NF1 Latin1 (ISO1)
018 OKI C830 OKIA3NF1 Latin1 (ISO1)
019 ES8430 OKIA3NF1 Latin1 (ISO1)
020 CX2633 MFP OKIA3NF1 Latin1 (ISO1)
021 OKI C5950 OKIA3NF1 Latin1 (ISO1)
022 OKI C5750 OKIA3NF1 Latin1 (ISO1)
023 OKI C6150 OKIA3NF1 Latin1 (ISO1)
024 ES2632a4 OKIA3NF1 Latin1 (ISO1)
025 OKI MC560 OKIA3NF1 Latin1 (ISO1)
026 ES5460 MFP OKIA3NF1 Latin1 (ISO1)
027 CX2033 MFP OKIA3NF1 Latin1 (ISO1)
028 OKI C9850 OKIA3WF1 Latin1 (ISO1)
029 OKI C9850 MFP OKIA3WF1 Latin1 (ISO1)
030 ES3640 Pro OKIA3WF1 Latin1 (ISO1)
031 ES3640 Pro MFP OKIA3WF1 Latin1 (ISO1)
032 CX3641 MFP OKIA3WF1 Latin1 (ISO1)
033 OKI MC860 OKIA3TR1 Turkey (ISO9)
034 ES8460 MFP OKIA3TR1 Turkey (ISO9)
035 OKI C830 OKIA3TR1 Turkey (ISO9)
036 ES8430 OKIA3TR1 Turkey (ISO9)
037 CX2633 MFP OKIA3TR1 Turkey (ISO9)
038 OKI C5950 OKIA3TR1 Turkey (ISO9)
039 OKI C5750 OKIA3TR1 Turkey (ISO9)
040 OKI C6150 OKIA3TR1 Turkey (ISO9)
041 ES2632a4 OKIA3TR1 Turkey (ISO9)
042 OKI MC560 OKIA3TR1 Turkey (ISO9)
043 ES5460 MFP OKIA3TR1 Turkey (ISO9)
044 CX2033 MFP OKIA3TR1 Turkey (ISO9)
045 OKI C711 OKIA4JP1 Japanese (SJIS)
046 OKI C610 OKIA4JP1 Japanese (SJIS)
047 OKI C530 OKIA4JP1 Japanese (SJIS)
048 OKI C830 OKIA4JP1 Japanese (SJIS)
049 OKI B431 OKBCJP01 Japanese (SJIS)
050 OKI B411 OKBCJP01 Japanese (SJIS)
051 OKI B840 OKBCJP02 Japanese (SJIS)
052 OKI B820 OKBCJP02 Japanese (SJIS)
053 OKI MC361 OKCCJP01 Japanese (SJIS)
054 OKI MC362 OKCCJP01 Japanese (SJIS)
055 OKI MC561 OKCCJP02 Japanese (SJIS)
056 OKI MC562 OKCCJP02 Japanese (SJIS)
057 OKI C841 OKCCJP02 Japanese (SJIS)
058 OKI C811 OKCCJP02 Japanese (SJIS)

059 OKI C531 OKCCJP02 Japanese (SJIS)
060 OKI C710 OKIA3NF1 Latin1 (ISO1)
061 OKI B710 OKIB700 Latin1 (ISO1)
062 OKI B720 OKIB700 Latin1 (ISO1)
063 OKI B730 OKIB700 Latin1 (ISO1)
064 ES7120 OKIB700 Latin1 (ISO1)
065 ES7130 OKIB700 Latin1 (ISO1)
066 OKI MPS730b OKIB700 Latin1 (ISO1)
067 OKI C610 OKA3UTF8 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
068 OKI C711 OKA3UTF8 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
069 ES6410 OKA3UTF8 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
070 ES7411 OKA3UTF8 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
071 OKI MB780 OKMB780 Latin1 (ISO1)
072 OKI MB790f OKMB790 Latin1 (ISO1)
073 OKI MB790m OKMB790 Latin1 (ISO1)
074 OKI MB471 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
075 OKI MB461 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
076 OKI MB451 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
077 OKI MB441 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
078 ES4161 MFP OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
079 OKI B431 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
080 OKI B411 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
081 OKI B401 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
082 ES4131 OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
083 OKI MB491 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
084 ES4191 MFP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
085 MPS4200mb OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
086 OKI C331 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
087 OKI C321 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
088 OKI MC362 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
089 OKI MC352 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
090 ES3452 MFP OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
091 OKI C841 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
092 OKI C831 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
093 ES8441 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
094 ES8431 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
095 OKI C531 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
096 ES5431 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
097 OKI MC562 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
098 ES5462 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
099 OKI C822 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
100 ES9460 MFP OKCCI102 Latin1 (ISO1)
101 ES9470 MFP OKCCI102 Latin1 (ISO1)
102 ES9460 MFP OKCCI202 Latin2 (ISO2)
103 ES9470 MFP OKCCI202 Latin2 (ISO2)
104 CX3535 MFP OKCCI101 Latin1 (ISO1)
105 CX4545 MFP OKCCI101 Latin1 (ISO1)
106 CX3535 MFP OKCCI201 Latin2 (ISO2)
107 CX4545 MFP OKCCI201 Latin2 (ISO2)
108 ES9160 MFP OKBCI101 Latin1 (ISO1)
109 ES9170 MFP OKBCI101 Latin1 (ISO1)

110 ES9160 MFP OKBCI201 Latin2 (ISO2)
111 ES9170 MFP OKBCI201 Latin2 (ISO2)
112 OKI C330 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
113 OKI C530 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
114 ES5430 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
115 OKI MB461+LP OKBCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
116 OKI MB491+LP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
117 MPS4700mb OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
118 OKI B841 OKBCJP02 Japanese (SJIS)
119 OKI B821 OKBCJP02 Japanese (SJIS)
120 OKI B801 OKBCJP02 Japanese (SJIS)
121 OKI MC862 OKCCJP02 Japanese (SJIS)
122 OKI MC852 OKCCJP02 Japanese (SJIS)
123 OKI MC861 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
124 OKI MC851 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
125 ES8461 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
126 ES8451 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
127 OKI MC862 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
128 OKI MC852 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
129 ES8462 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
130 MPS2731mc OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
131 OKI MC342 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
132 OKI MC332 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
133 OKI B731 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
134 OKI B721 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
135 ES7131 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
136 MPS5501b OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
137 OKI C931 OKCCJP03 Japanese (SJIS)
138 OKI C911 OKCCJP03 Japanese (SJIS)
139 ES9411 OKCCJP03 Japanese (SJIS)
140 OKI MC760 OKCCI103 Latin1 (ISO1)
141 OKI MC770 OKCCI103 Latin1 (ISO1)
142 OKI MC780 OKCCI103 Latin1 (ISO1)
143 ES7460 MFP OKCCI103 Latin1 (ISO1)
144 ES7470 MFP OKCCI103 Latin1 (ISO1)
145 ES7480 MFP OKCCI103 Latin1 (ISO1)
146 MPS3537mc OKCCI103 Latin1 (ISO1)
147 MPS4242mc OKCCI103 Latin1 (ISO1)
148 OKI MC760 OKCCI203 Latin2 (ISO2)
149 OKI MC770 OKCCI203 Latin2 (ISO2)
150 OKI MC780 OKCCI203 Latin2 (ISO2)
151 ES7460 MFP OKCCI203 Latin2 (ISO2)
152 ES7470 MFP OKCCI203 Latin2 (ISO2)
153 ES7480 MFP OKCCI203 Latin2 (ISO2)
154 MPS3537mc OKCCI203 Latin2 (ISO2)
155 MPS4242mc OKCCI203 Latin2 (ISO2)
156 OKI MB760 OKBCI102 Latin1 (ISO1)
157 OKI MB770 OKBCI102 Latin1 (ISO1)
158 ES7170 MFP OKBCI102 Latin1 (ISO1)
159 MPS5502mb OKBCI102 Latin1 (ISO1)
160 OKI MB760 OKBCI202 Latin2 (ISO2)

161 OKI MB770 OKBCI202 Latin2 (ISO2)
162 ES7170 MFP OKBCI202 Latin2 (ISO2)
163 MPS5502mb OKBCI202 Latin2 (ISO2)
164 OKI C931 OKCCUT03 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
165 OKI C911 OKCCUT03 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
166 ES9431 OKCCUT03 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
167 ES9411 OKCCUT03 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
168 ES9455 MFP OKCCI104 Latin1 (ISO1)
169 ES9465 MFP OKCCI104 Latin1 (ISO1)
170 ES9475 MFP OKCCI104 Latin1 (ISO1)
171 ES9455 MFP OKCCI204 Latin2 (ISO2)
172 ES9465 MFP OKCCI204 Latin2 (ISO2)
173 ES9475 MFP OKCCI204 Latin2 (ISO2)
174 OKI B432 OKBCJP02 Japanese (SJIS)
175 OKI B412 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
176 OKI B432 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
177 OKI B512 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
178 ES4132 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
179 ES5112 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
180 OKI MB472 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
181 OKI MB492 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
182 OKI MB562 OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
183 ES4192 MFP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
184 ES5162 MFP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
185 OKI MC873 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
186 OKI MC853 OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
187 ES8483 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
188 ES8473 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
189 ES8453 MFP OKCCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
190 OKI MC883 OKCCJP02 Japanese (SJIS)
191 OKI MC863 OKCCJP02 Japanese (SJIS)
192 ES8483 MFP OKCCJP02 Japanese (SJIS)
193 ES8463 MFP OKCCJP02 Japanese (SJIS)
194 ES4172LP MFP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
195 ES5162LP MFP OKBCUT02 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
196 OKI MC843 OKCCJP02 Japanese (SJIS)
197 OKI MC573 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
198 ES5473 MFP OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
199 OKI MC363 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
200 OKI C542 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
201 OKI C532 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
202 ES5442 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
203 ES5432 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
204 OKI C332 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
205 OKI C712 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
206 OKI C612 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
207 ES7412 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
208 ES6412 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
209 OKI C843 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
210 OKI C833 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
211 OKI C823 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)

212 ES8443 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
 213 ES8433 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
 214 OKI MC573 OKCCJP01 Japanese (SJIS)
 215 OKI MC363 OKCCJP01 Japanese (SJIS)
 216 OKI C542 OKCCJP01 Japanese (SJIS)
 217 OKI C532 OKCCJP01 Japanese (SJIS)
 218 OKI C332 OKCCJP01 Japanese (SJIS)
 219 OKI C712 OKCCJP01 Japanese (SJIS)
 220 OKI C612 OKCCJP01 Japanese (SJIS)
 221 OKI C813 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
 222 ES9466 MFP OKCCI105 Latin1 (ISO1)
 223 ES9476 MFP OKCCI105 Latin1 (ISO1)
 224 ES9466 MFP OKCCI205 Latin2 (ISO2)
 225 ES9476 MFP OKCCI205 Latin2 (ISO2)
 226 OKI MC563 OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
 227 ES5463 MFP OKCCUT01 Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)

Details:

[Device type]

OKI440

[Printer models]

OKI B440

OKI B430

OKI B420

OKI B410

ES4140

OKI MB460

OKI MB470

OKI MB480

ES4160 MFP

ES4180 MFP

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKIB6500

[Printer models]

OKI B6500

OKI B6250

ES6150

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Output trays
- Double-sided Printing
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

[Device type]

OKIB930

[Printer models]

OKI B930

ES9130

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Output trays
- Double-sided Printing
- Stapling
- Punching
- Job Separation
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

[Device type]

OKIA3NF1

[Printer models]

OKI MC860

ES8460 MFP

OKI C830

ES8430

CX2633 MFP

OKI C5950

OKI C5750

OKI C6150

ES2632a4

OKI MC560

ES5460 MFP

CX2033 MFP

OKI C710

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
 - Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- OKI MC560, ES5460 MFP, CX2033 MFP
- Note that SNMP status feedback does not work correctly with these devices so should not be used.
- Other models
- Other models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKIA3WF1

[Printer models]

OKI C9850

OKI C9850 MFP

ES3640 Pro

ES3640 Pro MFP

CX3641 MFP

- Supported language: Latin1 (ISO1)
- PDL: PCL

- Paper sizes: A3, A4, A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color
- Stapling
- Punching
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported, but require additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- Note that SNMP status feedback does not work correctly with these devices so should not be used.

[Device type]

OKIA3TR1

[Printer models]

OKI MC860

ES8460 MFP

OKI C830

ES8430

CX2633 MFP

OKI C5950

OKI C5750

OKI C6150

ES2632a4

OKI MC560

ES5460 MFP

CX2033 MFP

- Supported language: Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color
- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- OKI MC560, ES5460 MFP, CX2033 MFP

- Note that SNMP status feedback does not work correctly with these devices so should not be used.
- Other models
- Other models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKIA4JP1

[Printer models]

OKI C711

OKI C610

OKI C530

OKI C830

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
 - Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKIB700

[Printer models]

OKI B710

OKI B720

OKI B730

ES7120

ES7130

OKI MPS730b

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:

- Input trays
- Output trays
- Double-sided Printing
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

[Device type]

OKA3UTF8

[Printer models]

OKI C610

OKI C711

ES6410

ES7411

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
 - Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
 - SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.
 - Printer firmware CU3.02 or above is required.

[Device type]

OKMB780

[Printer models]

OKMB780

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome laser printer
- Additional print options:

- Input trays
- Output tray selection
- Double-sided Printing
- Password protection
- Vendor-defined (2-up printing)

[Device type]

OKMB790

[Printer models]

OKI MB790f

OKI MB790m

- Supported language: Latin1 (ISO1)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome laser printer
- Additional print options:
- Input trays
- Output tray selection
- Double-sided Printing
- Password protection
- Vendor-defined (2-up printing)

[Device type]

OKCCI101

[Printer models]

CX3535 MFP

CX4545 MFP

- PDL: PCL
 - Scripts/Languages: Latin1 (ISO1)
 - Graphics: Yes
 - OCR: No
 - Printer-resident bar code: No
 - Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
 - Color: Yes
 - Input trays: Yes (See [POSS] section for details.)
 - SNMP Job status feedback: No
 - POSS (Print Options for SAPScripts and Smartforms)
- * denotes the default value in the device type file
- Print Mode: *Normal, Proof, Private, Hold
- Collate: *Sort, Group, Rotated Sort
- Duplex: *None, Long Edge, Short Edge
- Orientation: *Portrait, Landscape
- Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
- Output tray: Tray 1, *Tray 2, Inner Tray
- Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
- Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCC1102

[Printer models]

ES9460 MFP

ES9470 MFP

- PDL: PCL
- Scripts/Languages: Latin1 (ISO1)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCC1103

[Printer models]

OKI MC760

OKI MC770

OKI MC780

ES7460 MFP

ES7470 MFP

ES7480 MFP

MPS3537mc

MPS4242mc

- PDL: PCL

- Scripts/Languages: Latin1 (ISO1)

- Graphics: Yes

- OCR: No

- Printer-resident bar code: No

- Paper sizes: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL

- Color: Yes

- Input trays: Yes (See [POSS] section for details.)

- SNMP Job status feedback: No

- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: *Tray 1, Inner Tray

Stapling: *None, Top Left, Top Right

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCC1104

[Printer models]

ES9455 MFP

ES9465 MFP

ES9475 MFP

- PDL: PCL

- Scripts/Languages: Latin1 (ISO1)

- Graphics: Yes

- OCR: No

- Printer-resident bar code: No

- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

- Color: Yes

- Input trays: Yes (See [POSS] section for details.)

- SNMP Job status feedback: No

- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCCI105

[Printer models]

ES9466 MFP

ES9476 MFP

- PDL: PCL
- Scripts/Languages: ISO1+UPE (Latin 1+Unicode Print Enable)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold, Anywhere

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom,

Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Project Code: Yes (63 characters)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCCI201

[Printer models]

CX3535 MFP

CX4545 MFP

- PDL: PCL

- Scripts/Languages: Latin2 (ISO2)

- Graphics: Yes

- OCR: No

- Printer-resident bar code: No

- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

- Color: Yes

- Input trays: Yes (See [POSS] section for details.)

- SNMP Job status feedback: No

- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCCI202

[Printer models]

ES9460 MFP

ES9470 MFP

- PDL: PCL

- Scripts/Languages: Latin2 (ISO2)

- Graphics: Yes

- OCR: No

- Printer-resident bar code: No

- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

- Color: Yes

- Input trays: Yes (See [POSS] section for details.)

- SNMP Job status feedback: No

- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart
 Halftone: *Auto, Smooth, Detail
 Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Pure black: Yes
 Pure gray: Yes
 Black overprint: Yes

[Device type]

OKCCI203

[Printer models]

OKI MC760

OKI MC770

OKI MC780

ES7460 MFP

ES7470 MFP

ES7480 MFP

MPS3537mc

MPS4242mc

- PDL: PCL
- Scripts/Languages: Latin2 (ISO2)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: *Tray 1, Inner Tray

Stapling: *None, Top Left, Top Right

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[Device type]

OKCCI204

[Printer models]

ES9455 MFP

ES9465 MFP

ES9475 MFP

- PDL: PCL

- Scripts/Languages: Latin2 (ISO2)

- Graphics: Yes

- OCR: No

- Printer-resident bar code: No

- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

- Color: Yes

- Input trays: Yes (See [POSS] section for details.)

- SNMP Job status feedback: No

- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin

color - 2KM, Twin color - 2KY, Twin color - 2KW
 Image quality type: *Normal, Photo, Presentation, Lineart
 Halftone: *Auto, Smooth, Detail
 Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Pure black: Yes
 Pure gray: Yes
 Black overprint: Yes

[Device type]

OKCCI205

[Printer models]

ES9466 MFP

ES9476 MFP

- PDL: PCL
- Scripts/Languages: Latin2 (ISO2)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold, Anywhere
 Collate: *Sort, Group, Rotated Sort
 Duplex: *None, Long Edge, Short Edge
 Orientation: *Portrait, Landscape
 Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
 Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
 Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
 Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double
 User login: Yes
 Department code: Yes (5 digit numbers)
 Project Code: Yes (63 characters)
 Number of copies: 1-999
 Booklet: Yes
 Font pitch: Yes
 Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: *Normal, Photo, Presentation, Lineart
 Halftone: *Auto, Smooth, Detail
 Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
 Pure black: Yes
 Pure gray: Yes
 Black overprint: Yes

[Device type]

OKBC1101

[Printer models]

ES9160 MFP

ES9170 MFP

- PDL: PCL
- Scripts/Languages: Latin1 (ISO1)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold
 Collate: *Sort, Group, Rotated Sort
 Duplex: *None, Long Edge, Short Edge
 Orientation: *Portrait, Landscape
 Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
 Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
 Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
 Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double
 User login: Yes
 Department code: Yes (5 digit numbers)
 Number of copies: 1-999
 Booklet: Yes
 Font pitch: Yes

[Device type]

OKBC1102

[Printer models]

OKI MB760
 OKI MB770
 ES7170 MFP
 MPS5502mb

- PDL: PCL
- Scripts/Languages: Latin1 (ISO1)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
- Color: No
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: *Tray 1, Inner Tray

Stapling: *None, Top Left, Top Right

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

[Device type]

OKBCI201

[Printer models]

ES9160 MFP

ES9170 MFP

- PDL: PCL
- Scripts/Languages: Latin2 (ISO2)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
- Color: Yes
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
 Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
 Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree
 Rotation, Short Edge with 180 degree Rotation
 Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
 User login: Yes
 Department code: Yes (5 digit numbers)
 Number of copies: 1-999
 Booklet: Yes
 Font pitch: Yes

[Device type]

OKBCI202

[Printer models]

OKI MB760

OKI MB770

ES7170 MFP

MPS5502mb

- PDL: PCL
- Scripts/Languages: Latin2 (ISO2)
- Graphics: Yes
- OCR: No
- Printer-resident bar code: No
- Paper sizes: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
- Color: No
- Input trays: Yes (See [POSS] section for details.)
- SNMP Job status feedback: No
- POSS (Print Options for SAPScripts and Smartforms)

* denotes the default value in the device type file

Print Mode: *Normal, Proof, Private, Hold

Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge

Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: *Tray 1, Inner Tray

Stapling: *None, Top Left, Top Right

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

[Device type]

OKCCJP01

[Printer models]

OKI MC361

OKI MC362

OKI MC573

OKI MC363
 OKI C542
 OKI C532
 OKI C332
 OKI C712
 OKI C612

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKCCJP02

[Printer models]

OKI MC561
 OKI MC562
 OKI C841
 OKI C811
 OKI C531
 OKI MC862
 OKI MC852
 OKI MC883
 OKI MC863
 ES8483 MFP
 ES8463 MFP
 OKI MC843

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color

- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKCCJP03

[Printer models]

OKI C931

OKI C911

ES9411

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Output trays
- Double-sided Printing
- Print in color
- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKBCJP01

[Printer models]

OKI B431

OKI B411

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI

- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKBCJP02

[Printer models]

OKI B840

OKI B820

OKI B841

OKI B821

OKI B801

OKI B432

- Supported language: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKCCUT01

[Printer models]

OKI C331

OKI C321

OKI MC362
 OKI MC352
 ES3452 MFP
 OKI C330
 OKI MC342
 OKI MC332
 OKI MC573
 ES5473 MFP
 OKI MC363
 OKI C542
 OKI C532
 ES5442
 ES5432
 OKI C332
 OKI C712
 OKI C612
 ES7412
 ES6412
 OKI C843
 OKI C833
 OKI C823
 ES8443
 ES8433
 OKI C813
 OKI MC563
 ES5463 MFP

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKCCUT02

[Printer models]

OKI C841

OKI C831
 ES8441
 ES8431
 OKI C531
 ES5431
 OKI MC562
 ES5462 MFP
 OKI C822
 OKI C530
 ES5430
 ES7411
 ES6410
 OKI MC861
 OKI MC851
 ES8461 MFP
 ES8451 MFP
 OKI MC862
 OKI MC852
 ES8462 MFP
 MPS2731mc
 OKI MC873
 OKI MC853
 ES8483 MFP
 ES8473 MFP
 ES8453 MFP

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Print in color
- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKCCUT03

[Printer models]

OKI C931

OKI C911
 ES9431
 ES9411

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
- Input trays
- Output trays
- Double-sided Printing
- Print in color
- Password protection
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKBCUT01

[Printer models]

OKI MB471

OKI MB461

OKI MB451

OKI MB441

ES4161 MFP

OKI B431

OKI B411

OKI B401

ES4131

OKI MB461+LP

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
- Input trays
- Double-sided Printing
- Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM,

RSPOS and RUECKNR are supported without additional hardware.

- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[Device type]

OKBCUT02

[Printer models]

OKI MB491

ES4191 MFP

MPS4200mb

OKI MB491+LP

MPS4700mb

OKI B731

OKI B721

ES7131

MPS5501b

OKI B412

OKI B432

OKI B512

ES4132

ES5112

OKI MB472

OKI MB492

OKI MB562

ES4192 MFP

ES5162 MFP

ES4172LP MFP

ES5162LP MFP

- Supported language: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Password protection
 - Barcode Printing
- ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

This document refers to

SAP Note/KBA	Title
1097990	List of Printer Vendor Wizard Notes

This document is referenced by

SAP Note/KBA	Title
1097990	List of Printer Vendor Wizard Notes

Attachments

File Name	File Size	Mime Type
OKI_DevTyps.zip	1767	application/x-zip-compressed

[Terms of use](#) | [Copyright](#) | [Trademark](#) | [Legal Disclosure](#) | [Privacy](#)