

# ML395B Specifications

**OKI**  
Open up your dreams



## A fast, versatile and reliable 24-pin printer, with low running cost

### High quality, high volume perfect for demanding environments

The ML395B delivers relentless, high speed, high volume output. With flexible paper handling capability, these impact printers are suitable where heavy duty word and high volume data processing are required.

### The fastest in their class

Each of the four print speeds is amongst the fastest in its class

- At 607 characters per second (cps), the High-Speed Draft mode blasts through spreadsheet reports in no time
- The 485cps Utility and 245cps Utility Near Letter Quality modes deliver drafts and memos at speed
- The 165cps Letter Quality mode delivers crisp, clear correspondence and proposals on demand

### Flexible media and forms handling

The ML395B optional bottom push tractor and the bottom feed's straight-through paper path are perfect for labels, card stock and forms with up

to 5 parts. The top feed is ideal for single sheets and envelopes and the rear push feed for fanfold paper.

A time-saving 'paper park' function lets you switch forms at the push of a button and the zero-tear function advances a printed page to the perforation and lets you tear it off cleanly and precisely, whilst automatically positioning the next page ready for printing.

### OKI's commitment to customers

The OKI brand is one of proven reliability and value. We provide printers that increase our customers' long-term business performance without impacting their budget.

With almost half a century of experience in the impact printer industry, with OKI you are guaranteed a best-in-class, low cost, reliable and easy to use printer.

### Highlights:

- 136 column dot matrix printers
- OKI's unique, high durability 24-pin printhead
- Multi-part paper-handling (original + 3 copies)
- Up to 607cps print speed
- Letter quality 24-pin print
- Crisp clear printing, even on 5-part forms
- Eight scalable barcodes and four text fonts
- 5 million character mono ribbon life
- Zero-tear capability through any paper path, with auto-advance

**Variants available:**  
**ML395B**  
Mono version



## ML395B - Dot Matrix Printers

| PRINTER                                 |  | GENERAL FEATURES                    |   |
|---|--|-------------------------------------|---|
| Number of pins                          | 24   | Input buffer                        | 23Kbytes  |
| Columns                                 | 136 (10cpi); 272 (maximum in compression mode)   | Power supply                        | Single phase 220 to 240VAC, +/- 10%, frequency 50/60Hz, +/- 2%                                    |
| Character pitch                         | 10/12/15/17.1/20 pitch and proportional  | Power consumption                   | Operating: 300W; Non-operating: 60W   |
| Graphics resolution                     | Up to 240 x 360dpi   | Noise level                         | 58dB(A); 56dB(A) (quiet mode)   |
| Print speed                             | Fastest Print Speed: 607cps; Utility: 486cps (12cpi), 405cps (10cpi); Letter Quality: 162cps (12cpi), 135cps (10cpi) | Dimensions (HxWxD)                  | 180 x 570 x 417mm   |
| <b>INTERFACE AND EMULATIONS</b>         |  | Weight                              | 17kg approx   |
| Interfaces                              | Centronics parallel interface, Serial RS 232C  | Print Head life                     | 200 million characters (average) in 10cpi Utility mode at normal 25% duty cycle, 35% page density |
| Emulations                              | Epson LQ, IBM ProPrinter X24E/X24E AGM   | Reliability                         | MTBF: 8,000 hours (duty cycle 25%, page density 35%)  |
| Typeface & font                         | HSD, Utility, NLQ, Courier, Roman, Swiss, Swiss Bold, Prestige, Gothic, Barcodes                                     | Product order numbers               | YA4050-3100G402   |
| Typestyle                               | Emphasised, Enhanced, Double Width, Double Height, Italics, Superscript, Subscript, Underline, Overscore             | <b>ACCESSORIES (ORDER NUMBERS)</b>  |   |
| <b>PAPER HANDLING</b>                   |  | Bottom push tractor                 | YA4043-4250G004   |
| Continuous paper                        | 76.2 - 406.4mm   | <b>CONSUMABLES (ORDER NUMBERS)</b>  |   |
| Continuous envelopes                    | 239 x 102mm  | Black Ribbon (5 million characters) | 45445201  |
| First printable line (from top of page) | Continuous (multi-parts): 23.3mm; Cut sheet (single sheet): 25.4mm   |                                     |   |
| Copy capability                         | Up to 1 original + 3 copies  |                                     |   |
| Paper feeding                           | Paper parking, Zero tear-off, Semi-autoload single sheet, Rear push tractors   |                                     |   |
| Optional paper feeding                  | Pull tractor, Bottom push tractor  |                                     |   |

**Consumables Information:** Only use genuine OKI Original consumables to ensure the best quality and performance from your hardware. Non OKI Original products may damage your printer's performance and invalidate your warranty.

**Okidata (Singapore) Pte Ltd**  
438A Alexandra Road  
#02-11/12,  
Lift Lobby 3,  
Alexandra Technopark,  
Singapore 119967  
Tel: (65) 6221 3722  
[www.oki.com/sg/printing](http://www.oki.com/sg/printing)

**Okidata (S) Pte Ltd**  
**Malaysia Branch Office**  
Suite 21.03, 21st Floor,  
Menara IGB, Mid Valley City,  
59200 Kuala Lumpur, Malaysia  
Tel: (03) 2287 1177  
Tel: 1800 88 1177 (Toll Free)  
Fax: (03) 2287 1166  
[www.oki.com/my/printing](http://www.oki.com/my/printing)

**Okidata Systems (Thailand) Ltd**  
1168/63 Lumpini Tower, 22nd Floor,  
Rama IV Road., Tungmahamek, Sathorn  
Bangkok Thailand 10120  
Tel: (662) 679 9235  
Fax: (662) 679 9243, 45  
[www.oki.com/th/printing](http://www.oki.com/th/printing)

# OKI