

A3 colour MFP for large workgroups and busy departments

Productive, secure, efficient and easy to use. These A3 colour multi-function products can bring paper feed versatility, maximum performance and workflow productivity.

The ES9466 MFP and ES9476 MFP offer High Definition colour printing and superior performance enabling users to generate a wide range of professional documents in-house. With advanced security features and seamless integration with document workflows, users can be their most productive and efficient even when dealing with confidential documents.

Enhanced efficiency through ease of use

Designed to be used by many, the intuitive touch screen can be customised for each and every user to ensure maximum productivity.

- 9" (23cm) tablet-style colour touch screen
- Menu functions, user icons and the display background can be customised for individual user-setup



- The 300-sheet Dual Scan Document Feeder (DSDF) model scans documents at 240 images per minute (ipm)
- The 100-sheet Reversing Automatic Document Feeder (RADF) model scans documents at 73ipm

Flexible open architecture for simple integration into your document workflow

The embedded platform, sXP (Smart Extendable Platform), enhances productivity by allowing users to electronically capture, distribute and manage document workflows.

- Customisable open architecture for ease of integration
- Access to document management software SENDYS Explorer LITE at no cost

- Scan preview to ensure the correct image is input to the workflow process
- Store commonly printed documents in your personal inbox for easy retrieval with E-Filing



ES9466 MFP with RADF and Cabinet

Flexible configuration for efficient productivity

Select the configuration and paper output options including several finishers to meet your business needs.

- Paper feeder options available: 1,200-sheet Cabinet, 1,750-sheet Paper Feed Pedestal (PFP) or 3,200-sheet Large Capacity Feeder (LCF)
- 100-sheet Multi-Purpose Tray (MPT)
- Paper sizes from A6 to SRA3
- Print on stock from 60 to 280gsm
- A4 print/copy speeds up to 50ppm
- Time to first copy, from 5.7 secs colour and 4.4 secs mono (ES9476 MFP)
- High capacity 38.4k mono and 33.6k colour toner cartridge
- Finishing options include:
 - 2-tray Inner Finisher (IF)
 - Multi-Stapling Finisher (MSF)
 - Saddle-Stitch Finisher (SSF)

Print smart - by printing in-house

Excellent print quality and versatile paper handling produces high quality professional documents, on a multitude of different media in-house, without having to rely on a professional print house or a high street print shop.

- Advanced image processing
- Wide range of paper weights, sizes and types
- ICC colour profiles
- Extensive output options from posters to booklets and banners up to 1.2m long

Advanced security to protect your business

Advanced security features to preserve the confidentiality of sensitive data. Sophisticated user authentication prevents unauthorised access. There is an option to mount a Smart Card Reader in the machine for easy system integration.

- Secure Hard Disk Drive, with secure Data Overwrite option
- Secure networking with SNMPv3, SSL-Encryption
- Role Based Access Control
- Secure Print/PDF

Improving efficiency and your carbon foot print

A wide range of eco features help reduce energy consumption, environmental impact and ongoing costs.

- Sleep Mode - reduces standby power
- Duplex printing, copying, scanning and faxing[^] - reduces paper usage and enables printing in-house



ES9466 MFP with DSDF and Cabinet



ES9466 MFP with DSDF, PFP, Drawer Module and Inner Finisher installed



ES9466 MFP with DSDF, PFP, Drawer Module, Multi-Stapling Finisher and Hole punch Unit installed



ES9466 MFP with DSDF, PFP, Drawer Module, Saddle-Stitch Finisher and Hole Punch Unit installed

ES9466 MFP and ES9476 MFP - Colour and Mono Multifunction Products

PRINTER	
Print speed	ES9466 MFP: A4: 35ppm colour/mono; A3: 18ppm colour/mono ES9476 MFP: A4: 50ppm colour/mono; A3: 25ppm colour/mono
Time to first print	ES9466 MFP: Approx 7.8 seconds colour, 5.9 seconds mono ES9476 MFP: Approx 5.7 seconds colour 4.4 seconds mono
Warm up time	Power On: 20 seconds; Low-power mode and Sleep Mode: 12 seconds
Processor	Intel 1.33GHz Dual-Core
Resolution	600 x 600dpi, 5 bit; 1200 x 1200 dpi, 2 bit (PS only)
Printer fonts	80 PCL fonts & 136 PostScript fonts, PCL Bitmap fonts
SCANNER	
Resolution	Max. 600 x 600dpi
Speed	DSDF: Up to 240ipm (300 x 300dpi)
	RADF: Up to 73ipm (300 x 300dpi)
Colour depth	Output 24 bit (8 bit x 3 RGB)
Document input	DSDF: Up to 300 sheet and 1 sheet Platen
	RADF: Up to 100 sheet and 1 sheet Platen
Contrast	9 Levels
Format	JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page, Slim PDF, XPS-Multi/Single Page
Address book	LDAP & internal address book
Scan to	WS Scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Scan to e-Filing, Meta Scan (option)
COPY	
First copy out	ES9466 MFP: Approx 7.8 seconds colour, 5.9 seconds mono ES9476 MFP: Approx 5.7 seconds colour 4.4 seconds mono
Speed colour and mono	ES9466 MFP: A4: 35cpm; A3: 18cpm ES9476 MFP: A4: 50cpm; A3: 25cpm
Resolution	600 x 600dpi
Reduction / Enlargement	25-400% (platen), 25-200% (RADF) in 1% increments
Maximum copies	999
FAX (OPTIONAL)	
Connectivity	RJ11 x 2 (Line/Tel) PSTN
Speed	33.6kbps --2.4Kbps (automatic fallback)
Groups	Max. 200 groups, 400 destinations/group
Broadcast	Max. 400 destinations
Page memory	Max. 100 Jobs, 400 destinations/job, 2000 destinations, Max. 1000 pages/file
INTERFACE AND SOFTWARE	
Connectivity	10/100/1000baseT, 1 x Host USB 2.0 Front, 1 x Device USB 2.0
Printer languages	PCL5e, PCL5c, PCL6, PS3, PDF, XPS, JPEG
Network & protocols	10Base-T/100Base-TX Ethernet Card with internal Web Server for MFP and network card set-up and management. Includes POP3/APOP and SMTP Mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP:- ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), DHCP, SNMPv1/v3, DNS, Dynamic DNS, Secure DDNS, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols, NetBIOSoverTCP, Kerberos. NetWare 6.5 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via Novell NDPS Gateway. EtherTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:- EAP.
OS Compatibility ¹	Windows, Mac OS X, Linux
Advanced networking & security	IPv6 Phase2, IEEE2600.1, IEEE 802.1x, IPsec ² , SNMPv3, SSL3/TLS HTTPS encryption, Secure Erase ³ , Data Encryption ³ , MAC address filtering, IP address filtering, Secure Print
OPERATOR PANEL	
LCD Touch-screen	9" (23cm) tablet-style colour touch screen; 8 Hard Keys, 8 LED's

PAPER HANDLING	
Paper capacity (80gsm)	Standard / with Cabinet option: Tray 1: 550 sheets; Tray 2: 550 sheets; Multi-purpose tray: 100 sheets; DSDF: 300 sheets or RADF: 100 sheets
	with Paper Feed Pedestal (PFP) option: Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 550 sheets; Optional Tray 4: 550 sheets (Draw Module); Multi-purpose tray: 100 sheets; DSDF: 300 sheets or RADF: 100 sheets
	with Large Capacity Feeder (LCF) option: Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 2,000 sheets (A4 only); Multi-purpose tray: 100 sheets; DSDF: 300 sheets or RADF: 100 sheets
Maximum paper capacity	3,200 sheets of 80gsm
Paper sizes	Tray 1: A3, A4, A5, B4, B5; Tray 2/PFP/Drawer Module: SRA3, A3, A4, A5, B4, B5; LCF: A4; Multi-purpose tray: SRA3, A3, A4, A5 B4, B5, OHP. Support Custom size: Width 100-305mm Length 148-1200mm; DSDF/RADF: A3, A4, A5; Duplex: A3, A4, A5, B4, B5
Paper weight	Tray 1/2/PFP/Drawer Module: 60 to 256gsm; LCF: 64 to 105gsm; Multi-purpose tray: 52 to 280gsm; DSDF (Simplex/Duplex): 35 to 209gsm; RADF (Simplex): 35 to 157gsm; RADF (Duplex): 50 to 157gsm; Duplex: 60 to 256gsm
Duplex	Standard
Paper output	A4: 550 sheets of 80gsm; A3: 300 sheets of 80gsm
Options: paper output	Inner Finisher (IF): 2 trays, 600-sheet capacity; Multi-Stapling Finisher (MSF): 2 trays, 2,250-sheet capacity; Saddle-Stitch Finisher (SSF): 2 trays, 3,250-sheet capacity

GENERAL FEATURES	
Memory	Standard: 4GB RAM + 320GB HDD
Environment	Operating temperature/humidity: 10°C to 30°C / 20% to 85% RH
	Storage temperature/humidity: -10°C to 35°C / less than 85% RH (w/ supplies)
Power supply	Single phase 220–240VAC, frequency 50/60Hz
Power consumption	Max: 2000W; Sleep: <1W
Noise level	Operating: <71dB(A); Standby: <53dB(A); Power save: Background level
Dimensions (HxWxD)	DSDF: 1227 x 660 (max 948) x 640 (max 761) mm
	RADF: 1191 x 660 (max 948) x 640 (max 761) mm
Weight ⁴	DSDF: Cabinet: 105.6kg; PFP: 108.1kg; LCF: 117.3kg RADF: Cabinet: 103.6kg; PFP: 106.1kg; LCF: 115.3kg
Warranty	1 year standard parts warranty
Product order numbers	ES9466 MFP with RADF: 46557503RADF
	ES9466 MFP with DSDF: 46557503DSDF
	ES9476 MFP with RADF: 46557506RADF ES9476 MFP with DSDF: 46557506DSDF

ACCESSORIES (ORDER NUMBERS)	
Paper Feeders / Furniture	Cabinet: 45588602; PFP: 46557701; LCF: 46558101; Drawer Module: 46559901 (PFP only); Envelope Drawer: 46560001 (PFP only)
Finisher Units	MSF: 46560401; SSF: 46560501; IF: 46560301; Job Separator: 46560201; Bridge Kit: 46560601
Hole Punch Units	2 hole: 45011212 (IF); 2 hole: 45587412 (MSF or SSF)
Connectivity	Wireless LAN Module: 46559601; Fax Unit: 46559802
Enablers	Data Overwrite: 45518101; IPSec: 45518401; Meta Scan: 45518201; Embedded OCR (1 license): 46558601; Embedded OCR (5 license): 46558701; Multi-Station Print (1 license): 46558801; Multi-Station Print (5 license): 46558901
Other options	Manual Pocket: 46559301; Work Tray: 46559701; Panel 10 Key: 46559401; Card Reader Holder: 46558401; Harness Kit Coin Control: 46559201

OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road
Macquarie Park, NSW 2113
Australia
T 1800 800 140
WWW.OKIEXECUTIVESERIES.COM.AU

OKI DATA NEW ZEALAND

8 Antares Place, Rosedale
Auckland 0632
New Zealand
T 0800 654 669
WWW.OKIEXECUTIVESERIES.CO.NZ

⁴Fax is optional.

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²Optional IPsec Enabler required.

³Optional Disk Overwrite Kit required; ⁴Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Media Information: Certain types of media may not provide optimal results under default conditions.