

C332dn Specifications

Outstanding A4 colour printing for SMB at an affordable cost, delivering fast, reliable and high quality results for versatile jobs.

The C332dn brings professional high definition A4 colour printing to the desktop – helping small businesses build their brand and save outsourcing costs, all for a surprisingly affordable price.

Flexible media handling and high quality output, combined with large memory for graphics-rich documents, makes it ideal for printing marketing and other colour documents in-house - and at the fastest print speeds in the market. The C332dn meets everyday printing needs with many new advanced features packed into its sleek small footprint design.

Key features

- Outstanding, high definition ProQ2400 multi-level output quality, 1200 x 600dpi print resolution
- Flexible media handling – from A6 to 1320mm banners; card stock up to 220gsm
- Ultra-fast print speeds of up to 26ppm colour/30ppm mono
- Generous paper capacity of up to 880 sheets, with optional second tray
- 1GB RAM memory ensuring trouble-free printing of graphics-intensive documents
- Duplex printing as standard
- Citrix XenApp 7.6 compatibility - ideal for virtual network environment



Energy and cost saving functionality

- Print marketing materials in-house, thanks to outstanding print quality and media flexibility
- Deep Sleep mode saves energy, Auto-Off mode automatically powers down to less than 0.5W when not in use
- Toner Save to reduce cost, when printing draft or internal documents
- Duplex printing reduces paper usage
- Free consumables recycling programme
- Robust and long-lasting LED technology



Advanced connectivity

- Mobile printing from smartphones and tablets, Google Cloud Print 2.0 ready, as well as being compatible with AirPrint by Apple Inc
- Optional Wireless LAN Module available
- Wireless Direct feature offers safe, simultaneous connection of wired and wireless networking
- Gigabit Ethernet enables fast transfer of large colour files across the network

Simple to set-up, use and own

- Easy to set-up and get started
- Quiet mode ideal for smaller offices
- Video guidance for installation and changing consumables
- When new features are available you can update the device via the OKI portal

A4	✓
Colour/Mono	✓
Duplex/Networked	✓
Prints A6 to 1320mm, up to 220gsm	✓
1 – 5 users	✓

C332dn - Colour and Mono Printer

PRINTER	
A4 Print speed	26ppm colour, 30ppm mono
Time to 1st print	9 seconds colour, 8.5 seconds mono
Warm up time	Up to 60 seconds from power on and up to 32 seconds from power save
Processor Speed	667MHz

INTERFACE AND SOFTWARE	
Connectivity	USB 2.0 Device, 10Base-T/100Base-TX/1000Base-T Ethernet, Wireless IEEE802.11a/b/g/n (Optional)
Printer languages	PCL6 (XL3.0) and PCL5c, PostScript 3 (Emulation), IBM-ProPrinter, EPSON-FX, XPS, PDF (V1.7)
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP v4&v6, NetBIOS over TCP, DHCP, DHCPv6, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SNMPv1&v3, SNT, IPP, IPPS, WSD Print, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, AirPrint, Google Cloud Print, Wireless IEEE802.11a/b/g/n, WEP, WPA, WPA2, Personal, Enterprise
OS Compatibility¹	Vista (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 8 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8.1 (32-bit & 64-bit) / Server 2012 R2 (64-bit) / Windows 10 (32-bit & 64-bit); Linux PPD; Mac OS X 10.8.5 to 10.11
Advanced networking & security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encryption, MAC filtering, IP filtering, IPsec
Utility suite	Configuration Tool ² , Color Correct Utility, Color Swatch Utility ² , Driver Installer ² , Firmware Update Tool, Front End Installer ² , LPR Utility ² , Maintenance Utility ² , Network Card Setup ³ , Network Extension ² , PDF Print Direct ³ , Print Job Accounting Client, Profile Assistant ³ , PS Gamma Adjuster, smart PrintSuperVision ² , Template Manager ² , Web Driver Installer ²

TYPEFACES	
Printer fonts	Scalable: 87 PCL Fonts and 80 PostScript fonts, PCL Bitmap fonts: Lineprinter, OCR-A/B, USPS ZIP Barcode
Barcode	10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET, 2 types of two dimensions: PDF417, QR code

PRINT QUALITY	
Resolution	ProQ2400 Multi-level Technology, 1200 x 600dpi, 600 x 600dpi
Enhancements	Auto Color Balance, Photo Enhance via driver (Windows PCL6 driver only)

PAPER HANDLING	
Paper capacity	Tray 1: 250 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional 2nd tray	530 sheets of 80gsm
Maximum paper capacity	880 sheets of 80gsm
Paper sizes	Tray 1: A4, A5, B5, A6, B6; Tray 2: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, B6, B6 Half, Envelopes (C5, DL, Com-9, Com-10, Monarch), Index Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x 150mm, 125 x 175mm), Custom Size (up to 1320mm length including banners); Duplex: A4, A5, B5
Paper weight	Tray 1/2: 64 to 176gsm; Multi-purpose tray: 64 to 220gsm; Duplex: 64 to 176gsm
Duplex	Standard
Paper output	Face Down: 150 sheets of 80gsm; Face Up: 100 sheets of 80gsm

¹Check local OKI website for latest driver releases and OS compatibility; ²Windows only; ³Mac only; ⁴Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

GENERAL FEATURES	
Memory	1GB RAM; 3GB eMMC
Environment	Operating temperature/humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended) Storage temperature/humidity: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption	Typical: 540W; Max: 1170W; Idle: 90W; Power Save: <14W; Deep Sleep: <1.1W; Auto-Off: <0.5W
Noise level	Operating: 52dB(A); Standby: 37dB(A); Power save: Inaudible
Dimensions (WxDxH)	410 x 504 x 242mm
Weight⁴	22kg
Duty cycle	Maximum: 45,000 pages/month; Recommended: Up to 5,000 pages/month
Product order number	C332dn: 46403103

ACCESSORIES (ORDER NUMBERS)	
2nd paper tray	44472103
Wireless LAN Module	45830202

CONSUMABLES (ORDER NUMBERS)	
Toner cartridges* (1,500 pages)	Cyan: 46508723; Magenta: 46508722; Yellow: 46508721; Black: 46508724
Toner cartridges* (3,000 pages)	Cyan: 46508719; Magenta: 46508718; Yellow: 46508717
Toner cartridge* (3,500 pages)	Black: 46508720
Image drum**	44968302
Transfer Belt (60,000 pages)	44472203
Fuser Unit (60,000 pages)	44472604

*Toner: A4 pages yield compliant with ISO/ISC 19798.

Printer shipped with a starter cartridge for the average 1,000 pages yield in case of A4 single side continuous printing with the ISO test pattern.

**Drum: Average life of 3 pages per job from tray 1 in simplex mode (up to 30,000 pages in black, 20,000 pages in colour).

Okidata (Singapore) Pte Ltd
438A Alexandra Road
#02-11/12,
Lift Lobby 3,
Alexandra Technopark,
Singapore 119967
Tel: (65) 6221 3722
www.oki.com/sg/printing

Okidata (Singapore) Pte Ltd
Malaysia Branch Office
Suite 21.03, 21st Floor,
Menara IGB, Mid Valley City,
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
Tel: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
www.oki.com/my/printing

Okidata Systems (Thailand) Ltd
1168/63 Lumpini Tower, 22nd Floor,
Rama IV Road., Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243/245
www.oki.com/th/printing

